



STAATSKOERANT
VAN DIE REPUBLIEK VAN SUID-AFRIKA

REPUBLIC OF SOUTH AFRICA
GOVERNMENT GAZETTE



REGULASIEKOERANT No 1475

As 'n Nuusblad by die Poskantoor Geregistreer

PRYS 10c PRICE
OORSEE 15c OVERSEAS
POSVRY—POST FREE

REGULATION GAZETTE—No 1475
Registered at the Post Office as a Newspaper

VOL 73]

PRETORIA 23 JULIE 1971
23 JULY

[No 3219

GOEWERMENSKENNISGEWING

DEPARTEMENT VAN NYWERHEIDSWESE

No R 1266 23 Julie 1971

WET OP STANDAARDE 1962

STANDAARDBOUREGULASIES—
VERBETERINGS

Goewermentskennisgewing R 1830 van 23 Oktober 1970 word hierby verbeter deur die volgende substitusies en/of byvoegings

GOVERNMENT NOTICE

DEPARTMENT OF INDUSTRIES

No R 1266 23 July 1971

STANDARDS ACT 1962

STANDARD BUILDING REGULATIONS—
CORRECTIONS

Government Notice R 1830 of 23 October 1970 is hereby corrected by the following substitutions and/or additions

KORREKSIËLYS/LIST OF CORRECTIONS

Hoofstuk/Reg Chapter/Reg	Bladsy Page	Skrap Delete	Vervang deur/voeg by Substitute/add
2, I, 3 (2) (d) (iii)	6 7	1 25 1 25	1 20 1 20
2, I, 5 (a) (ii) (iii)	11 11	Vierdiepings Vierdiepings	Verdiepings Verdiepings
2, I INDEX Plans	28	Power of entry 12 14	—
Between Preliminary and Prohibited	28	—	Power of entry 12 14
2, II 1 Footnote 1 Voetnoot 2	2 3	explanatory memorandum verduidelikende memorandum	introductory note inleidende opmerking
2, II, 6 (b) (iii)	6 7	1 25 1 25	1 20 1 20
2, II 11	11	Ingenieur	Plaaslike Bestuur
2, II 23 Voetnoot 14	19	—	14
2, II, 41 Footnote 22 Voetnoot 22	26 27	explanatory memorandum verduidelikende memorandum	introductory note inleidende opmerking

Hoofstuk/Reg Chapter/Reg	Bladsy Page	Skrap Delete	Vervang deur/voeg by Substitute/add
2 III 1 Footnotes 1 4 5 Voetnoot 1, 2 4	2 3	explanatory memorandum verduidelikende memorandum	introductory note inleidende opmerking
2 III 6 (b) (iii)	6 7	1 25 1 25	1 20 1 20
2 IV 1 Footnotes 1 4 6 Voetnoot 2 4 6	2 3	explanatory memorandum verduidelikende memorandum	introductory note inleidende opmerking
2 IV 1 (I) Footnote 8 Voetnoot 8	4 5	explanatory memorandum verduidelikende memorandum	introductory note inleidende opmerking
2, IV 5 (b) (iii)	6 7	1 25 1 25	1 20 1 20
2 IV 32 Footnotes 15, 16 Voetnoot 15 16	22 23	explanatory memorandum verduidelikende memorandum	introductory note inleidende opmerking
2 IV 39 Footnote 20 Voetnoot 20	26 27	explanatory memorandum verduidelikende memorandum	introductory note inleidende opmerking
3 4 Table I Col 4 Tabel I Kol 4	4 5	square vierkante	— —
Table II Col 2 Class V1 Tabel II Kol 2 Klas V1 Klas V2 Klas V3	6 7 7 7	gross vehicle weight voertuiggewig voertuiggewig voertuiggewig	gross vehicle mass voertuigmassa voertuigmassa voertuigmassa
3, App B Roofing materials	52	cubic metre	square metre
3 Aanh B Dakmateriaal	53	kubieke meter	vierkante meter
4 6 Formula Formule	4 5	$\frac{p}{q} \times b$	$p \times b$
Tabel I Voetnoot*	5	94 kilonewton	49 kilonewton <i>Opm</i> Hierdie drukfout kom nie in alle eksemplare voor nie
5, Tabel V/Table V Klas /Class III Kol /Col 2	18 19	4 50	6 3
Kol /Col 3	18 19	5 20	7 0
5, App B B 2 2nd line	54	be poured into a 200 millilitre measuring cylinder	be poured into a measuring cylinder of at least 200 millilitre capacity
5 Aanh B B 2, 2de reel B 2, 3de reel	55 —	van inhoudsmaat	2de reel Voeg in na maatsilinder met n inhoudsvermoe van minstens
6, Aanh C/App C Formula C Formule C	62 63	12 ³	π^3
8, 46 (b) 1st line Tabel XVI B/Table XVI B Col 1 Col 2 Kol 2	42 44 44 45	240 verdieping 218 (65-50 cavity -103) holte	140 — 217 (65-50 cavity -102) holte
8, Aanh D Kol 2/App D Col 2 Stainless Steel Vlekvrystaal	72 73	45	448

Hoofstuk/Reg Chapter/Reg	Bladsy Page	Skrap Delete	Vervang deur/voeg by Substitute/add
9 11-14	6	—	(Insert page No 6 Note This printing error does not appear in all copies)
14, 33 (4)	34	existing text	All treads and risers of interior stairs shall be so dimensioned that the product of the width of tread exclusive of nosing and the height of riser in millimetres shall be not less than 42 000 and not more than 55 000
	35	bestaande teks	Die afmetings van die loopstukke van binnetrappe moet so wees dat die produk van die loopstukbreedte uitgesonderd die neusrand en die hoogte van die stygstuk in millimeter minstens 42 000 en hoogstens 55 000 is
14 39 (a)	40 41	1 25 1 25	— —
14 56 (2) between last and 2nd last line	64	—	Insert the whole text printed above Reg 56 in the 2nd column from meter to "within

INHOUD

CONTENTS

No	BLADSY	No	PAGE
Nywerheidswese, Departement van GOEWERMENTSKENNISGEWING		Industries, Department of GOVERNMENT NOTICE	
R 1266 Wet op Staandaarde 1962 bouregulasies Verbeterings	Standaard 1	R 1266 Standards Act 1962 Regulations Corrections	Standard Building 1

